



FUSE TERMINAL THERMOPLASTIC SCREW TERMINAL
ON BOTH ENDS 10MM SZ1.5

Similar to image

Technical data:		
Type of mounting		standard mounting rail 35 mm
Length	mm	57
Color		miscellaneous
Terminal contact spacing	mm	10
Design of fuse holder		without
Design of the fuse link		others
Height of lowest mounting type	mm	42
Type of voltage / for supply of the fault indicator		others
Type of lamp / as fault indicator		without
Number of terminal levels		1
Combustibility class acc. to UL 94		Other
Insulation material		thermoplastic
Position / of terminal		lateral
Product component / required / connection plate		No
Operating voltage / rated value	V	250
Operating current / rated value	A	6.3
Design of the electrical connection		
• 1		screw-type terminal

• 2

Conductor cross-section that can be connected

- solid
 - minimum
 - maximum
- finely stranded
 - with wire end processing
 - minimum
 - maximum

screw-type terminal

mm ²	1
mm ²	1
mm ²	0.75
mm ²	1.5

Certificates/approvals:

General Product Approval



EG-Konf.

Shipping Approval



GL



PRS

other

[Environmental Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WA1011-1SF12/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1011-1SF12

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Sep 10, 2012