

TL-D 36W/865 1SL/25

927981386524



Product Description

Low-pressure mercury discharge lamps with a tubular 26 mm envelope

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

General Information

Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Life to 50% Failures (Nom)	15,000 h

Light Technical

Color Code	865 [CCT of 6500K]
Color Designation	Cool Daylight
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	85 lm/W
Color rendering index (CRI)	80

Operating and Electrical

Power Consumption	36 W
Lamp Current (Nom)	0.440 A
Voltage (Nom)	103 V

Controls and Dimming

Dimmable	Yes
----------	-----

Mechanical and Housing

Bulb Shape	T8
Net Weight (Piece)	0.140 kg

Approval and Application

Mercury (Hg) Content (Nom)	2.0 mg
----------------------------	--------


Product Data

Order product name	TL-D 36W/865 1SL/25
Full product name	TL-D 36W/865 1SL/25
Full product code	871829125462100
Local code description	TLD36W865ALTO

Order code	927981386524
Material Nr. (12NC)	927981386524
Local order code	TLD36W865ALTO
Numerator - Quantity Per Pack	1


EAN/UPC - Product/Case	8718291254621
Numerator - Packs per outer box	25
EAN/UPC - Case	8718291254638

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL-D 36W/865 1SL/25	28 mm	1,199.4 mm	1,206.5 mm	1,204.1 mm	1,213.6 mm

Photometric data




Spectral Power Distribution Colour - TL-D 36W/865 1SL/25


Lifetime



Life expectancy diagram - 3 hour cycle



Life expectancy diagram - 12 hour cycle



Lumen Maintenance Diagram - TL-D 36W/865 1SL/25