



Scotch® Rubber Mastic Tape 2228

Data Sheet

March 2023

Product Description

Scotch® Rubber Mastic Tape 2228 is a conformable self-fusing rubber electrical insulating and sealing tape. Scotch® Rubber Mastic Tape 2228 consists of an Ethylene Propylene Diene Monomer (EPDM) rubber backing coated with an aggressive, temperature-stable mastic adhesive. The tape is made 65 mils (1.65 mm) thick for quick application build-up. It is designed for electrical insulating and moisture sealing applications. Scotch® Rubber Mastic Tape 2228 is a UL recognized component for applications up to 130°C. It offers excellent resistance to moisture and ultraviolet exposure and is intended for both indoor and weather exposed outdoor applications.

Agency Approvals & Self Certifications

UL Component Recognized: UL510A Standard, Category OANZ2, File No. E17385

For Regulatory information including RoHS, REACH, please visit www.3M.com/regs

Product Features

- Conformable for application over irregular surfaces.
- Compatible with solid dielectric cable insulations.
- Self-fusing tape.
- Flexible over wide temperature range.
- Excellent weather and moisture resistance.
- Excellent adhesion and sealing characteristics with copper, aluminum and power cable jacket materials.
- Thick construction allows quick application build-up and padding over irregular connections.

Applications

- Primary electrical insulation for cable and wire connections rated up to 1000 volts.
- Electrical insulation and vibration padding for motor leads rated up to 1000 volts.
- Primary electrical insulation for bus bar connections rated up to 35kV (3M drawing 2047B-106)
- Padding for irregular shaped bus bar bolted connections.
- Moisture seal for cable and wire connections.
- Moisture seal for service drops.
- Moisture seal for ground wire and rod connections
- Jacket seal on power cable applications

Installation

Scotch® Rubber Mastic Tape 2228 should be applied in half-lapped layers until desired insulation build up is reached. Stretch the tape to 3/4 of its original width during application for good conformability and to obtain a moisture tight seal. Scotch® Rubber Mastic Tape 2228 should be overwrapped for mechanical protection with two half-lapped layers of Scotch® Super 33+™ Vinyl Electrical Tape.

Scotch® Rubber Mastic Tape 2228

Typical Properties

Properties	Typical Value
Temperature Rating ⁶	266°F (130°C)
Color	Black
Thickness ¹	65 mil (1.65mm)
Adhesion ⁵	Steel 15.0 lb/in (26.2 N/cm) PE 10.0 lb/in (17.5 N/cm)
Fusion ⁴	Pass (Type I)
Tensile Strength ¹	150 psi (1.03 N/mm ²)
Elongation ¹	1000 %
Dielectric Breakdown ¹ (Wet or Dry)	500 V/mil (19.7 kV/mm)
Dielectric Constant ¹	3.5
Dissipation Factor ¹	1.0 %
Water Absorption ³	0.15 %
Water Vapor Transmission Rate ²	0.1g/100in ² /24hr
Ozone Resistance ²	Pass
Heat Resistance ⁴	Pass, 130°C
UV Resistance ⁴	Pass

Note: These are typical values and should not be used for specification purposes.

* Foot notes: 1. ASTM-D-4325 Test method

2. ASTM-D-3833 Test method

3. ASTM-570 Test method

4. ASTM-D-4388 Test method

5. ASTM-D-1000 Test method

6. UL recognized component, Product Category OANZ2, and 3M File No. E17385

3M Water Seal Test

Samples were constructed using Scotch® Rubber Mastic Tape 2228 as a seal between PVC cable jackets and connecting ground wires (3M™ Cable Grounding Kit 2252). The specimens were thermal cycled in water baths at 25°C and 90°C. The total test time of 336 hours revealed no significant change in insulation resistance. The results meet requirements listed in UL 486D Standard for Insulated Wire Connectors for Use With Underground Connectors for insulation resistance (6.0 megohms, section 7.1) and dielectric voltage withstand (2.2kV, 1 minute, section 8.1).

Specification

The tape shall be 65 mils (1.65 mm) thick. The tape must be ethylene propylene rubber based and coated with a rubber mastic pressure-sensitive adhesive. The tape shall be a UL recognized component for applications up to 130°C. The tape must be applicable at temperatures of 0°C to 38°C without loss of physical properties. The tape must be classified for use in both indoor and weather-exposed outdoor environments. The tape must not split or crack when exposed to normal operating temperatures and environments. The tape must be compatible with synthetic cable and wire insulations. The tape shall not be corrosive to aluminum or copper conductors.

Shelf-Life

Scotch® Rubber Mastic Tape 2228 has a five-year shelf life (from date of manufacture) when stored in a humidity-controlled storage (10°C/50°F to 27°C/80°F and < 75% relative humidity). Good stock rotation is recommended.

Availability

Scotch® Rubber Mastic Tape 2228 available from 3M authorized distributors.

Also available from www.3M.com/electrical or call 800.245.3573.

Scotch® Rubber Mastic Tape 2228

TECHNICAL STATEMENT

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third-party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price. Warranty claims must be made within one (1) year from the date of 3M's shipment.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com

3M and Scotch are trademarks of 3M Company.



Electrical Markets Division
13011 McCallen Pass, Bldg. C
Austin, TX 78753
Phone: 800.245.3573
www.3M.com/electrical

Please Recycle. Printed in USA.
© 3M 2023. All Rights Reserved.
78-9237-0114-4 Rev D