

NICKEL PLATED BRASS GLAND - IP68 RATING - METRIC THREAD







This Metal Gland is a new unique product that is very different from traditional metal glands.

- IP68 rating - the highest possible.
- Superior strain relief
- Nickle plated brass for corrosion protection.
- Incorporates a unique 'camera shutter' principle which protects the cable.
- Fully insulated by plastic insert.
- Neoprene seal for fluid tightness.

The perfect gland for unarmoured PVC, XLPE and other synthetic cables.

Material
Brass nickle plated
Polyamide 6 insert - (self extinguishing)
Neoprene seal - (self extinguishing)
Neoprene O-Ring - (self extinguishing)

Continuous operating temperature
-20 to 100^{0}C

Chemical resistance
Resistant to normal organic solvents, mineral, animal and vegetable oil and fat, petrol.


Threading
According to IEC 423, IEC 423A and EN 60423


IP rating
IP68


Mounting Thread		Min.	Max.	Width	Product	Pack
A Dia. (mm)	B Leng. (mm)	Cab. Ran. (mm)	Cab. Ran. (mm)	A/F (mm)	Code	Code
12.0	5.0	3.0	6.0	14.0	HIP 68 - 12	40
16.0	5.0	5.0	10.0	17.0	HIP 68 - 16	20
20.0	6.0	8.0	13.0	22.0	HIP 68 - 20	20
25.0	7.0	11.0	17.0	27.0	HIP 68 - 25	10
32.0	8.0	15.0	21.0	34.0	HIP 68 - 32	5
40.0	8.0	19.0	28.0	43.0	HIP 68 - 40	3
50.0	9.0	26.0	35.0	55.0	HIP 68 - 50	1
63.0	10.0	32.0	42.0	65.0	HIP 68 - 63	1
75.0	14.50	48.0	62.0	80.0	HIP 68 - 75	1

NICKEL PLATED BRASS GLAND - IP68 RATING - PG THREAD









Mounting Thread		Min.	Max.	Width	Product
A Dia. (mm)	B Leng. (mm)	Cable Dia. (mm)	Cable Dia. (mm)	A/F (mm)	Code
7.0	6.0	2.0	2.0	14.0	HIP 68 - 7
9.0	6.0	4.0	8.0	17.0	HIP 68 - 9
11.0	6.0	5.0	10.0	20.0	HIP 68 - 11
13.5	7.0	6.0	12.0	22.0	HIP 68 - 13.5
16.0	7.0	9.0	14.0	24.0	HIP 68 - 16
21.0	8.0	12.0	17.0	30.0	HIP 68 - 21
29.0	8.0	18.0	25.0	26.0	HIP 68 - 29
36.0	16.0	22.0	32.0	50.0	HIP 68 - 36
42.0	16.0	30.0	38.0	58.0	HIP 68 - 42
48.0	16.0	32.0	42.0	34.0	HIP 68 - 48

HEX®
AN ISO 9001 COMPANY