



circuit breaker VL400N standard breaking capacity Icu=55kA, 415V AC 3-pole, line protection Trip Unit TM, LI In=315A, rated current IR=250...315A, overload protection, II=1575...3150A, short-circuit protection without auxiliary release without auxiliary/alarm switch, spare part product only for replacement purposes

Weight	5.7 kg
Net Weight	5.7 kg

Approvals / Certificates

Environment	General Product Approval
-------------	--------------------------

[Environmental Con-
firmations](#)

[Environmental Con-
firmations](#)



[Confirmation](#)



Test Certificates	other
-------------------	-------

[Special Test Certi-
cate](#)

[Confirmation](#)



[Miscellaneous](#)

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
Information for data generation and storage
<https://support.industry.siemens.com/cs/ww/en/view/109995012>
Information- and Downloadcenter (catalogues, leaflets,...)
<https://www.siemens.com/energy-automation>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL4731-1DC36-0AA0>
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3VL4731-1DC36-0AA0>
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL4731-1DC36-0AA0
CAx-Online-Generator
<https://www.siemens.com/cax>
Kennlinien
<https://curves.simaris.siemens.com/curves/3VL4731-1DC36-0AA0>



last modified: 11/24/2025

