DATASHEET - FUSE 160A 690V AR DIN 000 HSDNH



Fuse-link, high speed, 160 A, AC 690 V, 200 kA, DIN 000, aR, DIN, IEC, type T indicator, live gripping lugs

Powering Business Worldwide™

Part no. FUSE 160A 690V aR DIN 000 HSDNH
Catalog No. 170M1569D

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	160
Rated voltage			AC 690 V
Construction size			DIN 000
Utilization category			aR
Status indicator			type T indicator
Description			live gripping lugs
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with knife blade contacts
Standards/Regulations			DIN 43620 IEC 60269-4
Optional accessories			microswitches 170H0238, 170H0236

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	160
Rated voltage		V	690
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Combination fuse status indicator
Insulated metal gripping lugs (IMGL)			No

© 06/2021 by Eaton Industries GmbH