FICHA TECNICA

Producto	:	Selector amperimetrico
Marca	:	Salzer
Modelo	:	S16-61331
Amps	:	16A
Caract.	:	0-R-S-T 2 trafos
Certificac.	:	




AC Rating Code		Unit	S16/TP16/ RT16
Rated Operational Voltage(Ue)		V	690
Rated frequency		Hz	50/60
Rated impulse withstand Voltage(Uimp)		Kv	6
Rated Operational Current(Ie) AC21/AC1		A	16
Rated Uninterrupted Current (Ith)		A	20
Rated Operational Power			
AC23A "3 Ph , 415 V"		KW	7.5
		A	13
AC3		KW	5.5
"3 Ph , 415 V"		A	10
Short Circuit Capacity			
Rated Fuse Short Circuit Current		KA	5
Fuse Size (Type gG/gM)		A	16
Terminal Cross Section			
Single / Multiple	min	mm^2	1.5
	max	mm^2	4
Fine strand	min	mm^2	1
	max	mm^2	2.5
Terminal Cross Section		Metric	M3.5
Terminal Tightening Torque		Nm	0.8


CSA/UL Ratings

AC Rating Code		Unit	S16 TP16 RT16
Ampere Rating		A	15
Operational Voltage		V	600
HP Rating 1 Phase	120V	HP	0.33
	240V	HP	1
3 Phase	120V	HP	1.5
	240V	HP	3
	480V	HP	3
	600V	HP	5

61331



90 Degree



SELECTOR AMPERIMETRICO 1 POLO 2 TRANSFORMADORES

