

Soft Copper mm2

SOFT COPPER 16 mm2



Nexans Ref.: P00013075-3
Country Ref.: 10000066

CONTACT

Local Sales
 ventas.peru@nexans.com

APPLICATION

For grounding systems, directly buried, equipment protection and general purpose applications.

STANDARDS

PRODUCT

ASTM B3; ASTM B8; NTP 370.251

CONSTRUCTION

Conductor: Soft copper, class 2.

CROSS SECTION

From 6 mm2 up to 300 mm2.

PACKING

Non returnable wooden reels.

PRODUCT STANDARDS

NTP 370.251: Copper cables for overhead (bare or protected) and grounded.

CHARACTERISTICS

Construction characteristics

Conductor material	Soft copper
--------------------	-------------

Dimensional characteristics

Conductor cross-section	16 mm ²
Total number of wires	7
Wire diameter	1.69 mm
Conductor diameter	5.1 mm
Approximate weight	143 kg/km

Electrical characteristics

Max. DC resistance of the conductor at 20°C	1.13 Ohm/km
Perm current rating in air 30°C	141 A

Mechanical characteristics

Elongation	10 %
------------	------

Usage characteristics

Midspan	Yes
---------	-----

CALCULATION OF CURRENT CONDITION SOFT COPPER

CALCULATION OF CURRENT CONDITION

Maximum conductor temperature : 75°C.

Ambient air temperature : 30°C.