

Metasol Contactor
MC-22a/4



General

Product code	1347011100
Product description	MC-22a AC200V 50Hz 220V 60Hz 4P (Metasol) EXP (MC22A-40-00-LM7-S-E)
Main contact	4NO
Auxiliary contact	-
Control voltage	AC200V 50Hz
Type of terminal	Screw
Local/Export	Export
Standards	IEC 60947-4-1, IEC 60947-5-1, UL508
Certificates	CE, UL, CCC
	-

Characteristics

Number of poles	4P
Rated operational voltage [Ue]	690V
Rated insulation voltage [Ui]	690V
Rated withstand voltage [Uimp]	6kV
Rated frequency [Hz]	50Hz
Maximum operating rate in operating cycles per hour(AC3)	50Hz

Mechanical durability (mil. operations)	50Hz
Electrical durability (mil. operations)	50Hz
Rated operational current (AC-1)	50Hz
Power (AC-1)	15kW at 200/240V
	27kW at 380/440V
	35kW at 500/550V
	44kW at 690V
Current (AC-1)	40A at 200/240V
	40A at 380/440V
	40A at 500/550V
	40A at 690V
Motor power (AC-3)	-
	-
	-
	-
	-
Motor power (AC-4)	-
	-
Rated operational current (AC-3)	-
	-
	-
	-
	-
Rated operational current (AC-4)	-
	-
Rated operational current (DC-3,5)	-
	-

	-
Rated operational current (DC-1)	-
Type 2 Coordination	-
Motor power (UL/CSA)	2hp at 110~220V for 1 phase motors
	3hp at 220~240V for 1 phase motors
	7.5hp at 200~208V for 3 phase motors
	7.5hp at 220~240V for 3 phase motors
	10hp at 440~480V for 3 phase motors
	15hp at 550~600V for 3 phase motors
NEMA size	-
Rated Short-time withstand current	-
	-
	-
	-
	-
	-
Conductor size (AWG)	12~8
Conductor size (mm2)	2.5~10
The max. number of conductor	2.5~10
Conductor type	Solid, Stranded
Conductor characteristic	65/75? Cu-wire only
Main terminal size	M4
Crimp terminal (mm)	M4
Torque (lb-in)	M4
Torque (Nm)	M4
Torque (kgf.cm)	M4


Environment

Degree of protection	IP20
Ambient air temperature	-30? ~ +65? at storage
	-5? ~ +55? at operation (AC type)
Operating altitude	3000m(8900ft)
Shock resistance (1/2 sin wave=11ms)	8G at opened
	10G at closed
Vibration resistance (Conforming to IEC68-2-6) (5~300Hz)	2G at opened
	4G at closed
Flame resistance	V0 at conforming to UL94
	960? at conforming to IEC695-2-1
REACH	Yes
RoHS	Yes
WEEE	Yes

Dimensions

Weight	0.4kg
Size width	47.2mm / 1.86inch
Size height	80mm / 3.15inch
Size depth	86.8mm / 3.42inch

MC-22a/4 AC



Control coil

Control voltage	AC200V 50Hz
Control voltage limit [Uc]	85~110%
Consumption at 20°C	70VA at inrush
Consumption at 20°C	9VA at holding

Heat dissipation	2.3W at holding
Operating time	15~30ms at closing
Operating time	4~19ms at opening

Applicable Accessories

Metasol MS

Accessories

